







# Pneumatic Indicator Controller - Model SG80

## How to order

Use the tables below to select the unique specification of your SG80.

Example Code	SG80	1	2	3	W	Code Description
<b>Basic Model</b>	SG80					Model and Revision level
						<b>Control Action</b>
<b>Control action</b>		1				Proportional (P)
		2				Proportional and integral (P + I)
						<b>Pressure or temperature ranges</b>
<b>Pressure bar (psi) temperature ranges °C (°F)</b>		2				0/2.5 (0/36)
		3				0/4 (0/58)
		4				0/6 (0/87)
		5				0/10 (0/145)
		6				0/16 (0/232)
		7				0/25 (0/363)
		8				0/40 (0/580)
		K				0 to 70°C (32 to 158°F)
		L				0 to 100°C (32 to 212°F)
		M				0 to 150°C (32 to 302°F)
	N				0 to 250°C (32 to 482°F)	
						<b>Measuring element and connections</b>
<b>Measuring element and connections</b>		0				Standard temperature 2m capillary 3/4 BSP male
		1				Special temperature 6m capillary 3/4 BSP male
		2				Pressure 1/2 BSP male to 6mm tube
		3				Diaphragm seal
						<b>Mounting options</b>
<b>Mounting options</b>					W	Wall
					P	Panel

## **Europe and Africa**

---

AMOT  
Western Way  
Bury St Edmunds  
Suffolk, IP33 3SZ  
England

Tel +44 (0) 1284 762222  
Fax +44 (0) 1284 760256  
Email [info@amot.com](mailto:info@amot.com)

AMOT Controls GmbH  
Rondenbarg 25  
22525 Hamburg  
Germany

Tel +49 (0) 40 8537 1298  
Fax +49 (0) 40 8537 1331  
Email [germany@amot.com](mailto:germany@amot.com)

## **Asia and Australasia**